

Fibrex Standard is a North American pioneer in thin MDF offering customers flexibility, versatility and an unmatched range of finish options.

Fibrex Standard is ideal for furniture and cabinet components, chair backs, inserts, liners, gaming and decorative applications.

FIBREX STANDARD				
		St. Stephen, NB		
Thickness Range	(in./mm)	0.079 - 0.114" / 2mm - 2.9mm	0.118 - 0.154" / 3.0mm - 3.9mm	0.157 - 0.252" / 4.0mm - 6.4mm
Average MOR	(psi)	5,500	5,400	5,000
Average Internal Bond	(psi)	150	140	120
Un-sanded Thickness Tolerance	(in.)	+/- .010	+/- .010	+/- .012
Sanded Thickness Tolerance	(in.)	+/- .005	+/- .005	+/- .006
Length	(in.)	+/- 1/8	+/- 1/8	+/- 1/8
Width	(in.)	+/- 1/16	+/- 1/16	+/- 1/16
Squareness	(in.)	+/- 5/32	+/- 5/32	+/- 5/32

- Testing for conformance to the above specifications must be done in accordance with procedures described in the American National Standard for Medium Density Fiberboard (ANSI 208.2 2016 section 5.2 Sampling for Acceptance).
- Complies with formaldehyde emission requirements for MDF in CPA-ECC-2011, ANSI 208.2 2016 and CCR 93120.2 (CARB Composite Wood ATCM Phase II).
- All panels are approved for interior, non-structural application.
- Contains 100% Recycled/Recovered wood content.

California Proposition 65 Requirement:

Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection.

